



**NOTIFIED BODY No. 1293** 

### CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1293 - CPR - 0851 Rev.1

In compliance with the Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Intelligent analogue addressable sounder with base and built-in isolator module SensolRIS CSOU IS, Belinda CSOU IS, Erida CSOU IS, Marl CSOU IS, Smoke sense CSOU IS, Expera SSi

For specifications see Annex to this certificate

placed on the market under the name or trade mark of

# Teletek Electronics JSC 2, Iliyansko Shose Str., NPZ Voenna Rampa, 1220 Sofia, Bulgaria

and produced in the manufacturing plant

## Teletek Electronics JSC 2, Iliyansko Shose Str., NPZ Voenna Rampa, 1220 Sofia, Bulgaria

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 54-3:2001, EN 54-3:2001/A1:2002, EN 54-3:2001/A2:2006, EN 54-17:2005, EN 54-17:2005/AC:2007

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

#### constancy of performance of the construction product.

This certificate was first issued on November 6<sup>th</sup>, 2023 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Nová Dubnica, November 6th, 2023

Michal Mišiak

054733

EVPÚ a.s., Trenčianska 19, SK 018 51 Nová Dubnica, Slovak Republic, <u>www.evpu.sk</u> Page 1 / 2 FCO 425-13 Rev.1



#### General information

SensoIRIS CSOU IS (and derived varians) is an addressable sounder with base and built-in isolator module, compatible for mounting on all models standard bases for SensoIRIS devices. The sounder is designed for installing in addressable fire alarm systems which support operation via TTE communication protocol. The device is powered on from the panel and can be controlled via the communication protocol. The sounder supports 32 different tone types at two sound levels. The tone type and sound level are programmed from the control panel.

The sounder is compatible for operation with SensolRIS addressable detectors series: T110 (IS), S130 (IS) and M140 (IS).

The sounder is compatible for mounting on the following bases:

- 1. SensolRIS B124 Standard low profile base for addressable detectors and sounders.
- 2. SensoIRIS B124-HP Standard high profile base for addressable detectors and sounders.
- 3. SensolRIS VAD RST\* Standard base with built-in red LED flash beacons.
- 4. SensoIRIS VAD WST\* Standard base with built-in white LED flash beacons.
- \* The base SensoIRIS VAD RST/WST is specially designed for use with SensoIRIS CSOU IS sounders, as expands their application in fire alarm installations providing additional lighting indication in case of fire alarm events.

Technicalal specifications

Operating Voltage Range 16 – 32VDC

Sounder Type A
Material ABS

Dimensions Φ 105mm x 22mm

Weight ~ 120g

|   | Harmonised technical specification   |  |             |
|---|--|--|-------------|
| Essential characteristics   | EN 54-3:2001<br>EN 54-3:2001/A1:2002<br>EN 54-3:2001/A2:2006                           | EN 54-17:2005<br>EN 54-17:2005/<br>AC:2007 | Performance |
| Performance under fire conditions                                     | cl. 4.2, 4.3, 5.2, 5.3,<br>C.3.1=N/A, C.3.2=N/A,<br>C.5.1=N/A, C.5.2=N/A,<br>C.5.3=N/A | cl. 5.2                                    | Pass        |
| Operational reliability   | cl. 4.4, 4.5, 4.6, 5.4,<br>C4=N/A  | cl. 4                                      | Pass        |
| Durability of operational reliability: temperature resistance         | cl. 5.5, 5.6=N/A, 5.7, 5.8, 5.9  | cl. 5.4, 5.5                               | Pass        |
| Durability of operational reliability: humidity resistance            | cl. 5.8, 5.9, 5.10=N/A   | cl. 5.6, 5.7                               | Pass        |
| Durability of operational reliability: shock and vibration resistance | cl. 5.12 to 5.15   | cl. 5.9 to 5.12                            | Pass        |
| Durability of operational reliability: corrosion resistance           | cl. 5.11   | cl. 5.8                                    | Pass        |
| Durability of operational reliability: electrical stability           | cl. 5.16   | cl. 5.3, 5.13                              | Pass        |
| Durability of operational reliability: resistance to ingress          | cl. 5.17   |  | Pass        |

History of certification

| No. | Certificate No.     | Description                 | Date of issue                   |
|-----|---------------------|-----------------------------|---------------------------------|
| 1   | 1293-CPR-0851       | Original certificate issued | December 2 <sup>nd</sup> , 2022 |
| 2   | 1293-CPR-0851 Rev.1 | New location of the company | November 6th, 2023              |

Nová Dubnica, November 6th, 2023

Michal Mi ă i a k

Michal Mišiak

EVPÚ a.s., Trenčianska 19, SK 018 51 Nová Dubnica, Slovak Republic, <u>www.evpu.sk</u> Page 2 / 2 FCO 425-13 Rev.1