



FCC DOC TEST REPORT

According to

**47 CFR, Part 2, Part 15, CISPR PUB. 22,
ICES 003 Issue 6**

Applicant : ZHEJIANG DAHUA VISION TECHNOLOGY CO.,LTD.

Address : No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China

Equipment : HDCVI CAMERA

Model No. : DH-HAC-HFW2220RP-VF, DH-HAC-HFW2220RN-VF,
HAC-HFW2220RP-VF, HAC-HFW2220RN-VF,
DH-HAC-HFW2220RP-VF-IRE6, DH-HAC-HFW2220RN-VF-IRE6,
HAC-HFW2220RP-VF-IRE6, HAC-HFW2220RN-VF-IRE6,
DH-HAC-HFW2220RP-Z, DH-HAC-HFW2220RN-Z, HAC-HFW2220RP-Z,
HAC-HFW2220RN-Z, DH-HAC-HFW2220RP-Z-IRE6,
DH-HAC-HFW2220RN-Z-IRE6, HAC-HFW2220RP-Z-IRE6,
HAC-HFW2220RN-Z-IRE6, DH-HAC-HFW2120RP-Z,
DH-HAC-HFW2120RN-Z, HAC-HFW2120RP-Z, HAC-HFW2120RN-Z,
DH-HAC-HFW2120RP-Z-IRE6, DH-HAC-HFW2120RN-Z-IRE6,
HAC-HFW2120RP-Z-IRE6, HAC-HFW2120RN-Z-IRE6,
DH-HAC-HFW3100R-Z-IRE8, DH-HAC-HFW1200RP-VF,
DH-HAC-HFW1200RN-VF, HAC-HFW1200RP-VF, HAC-HFW1200RN-VF,
DH-HAC-HFW1200RP-VF-IRE6, DH-HAC-HFW1200RN-VF-IRE6,
HAC-HFW1200RP-VF-IRE6, HAC-HFW1200RN-VF-IRE6,
DH-HAC-HFW1100RP-VF, DH-HAC-HFW1100RN-VF,
HAC-HFW1100RP-VF, HAC-HFW1100RN-VF,
DH-HAC-HFW1100RP-VF-IRE6, DH-HAC-HFW1100RN-VF-IRE6,
HAC-HFW1100RP-VF-IRE6, HAC-HFW1100RN-VF-IRE6,
DH-HAC-HFW1220RP-VF, DH-HAC-HFW1220RN-VF,
HAC-HFW1220RP-VF, HAC-HFW1220RN-VF,
DH-HAC-HFW1220RP-VF-IRE6, DH-HAC-HFW1220RN-VF-IRE6,
HAC-HFW1220RP-VF-IRE6, HAC-HFW1220RN-VF-IRE6,
DH-HAC-HFW1400RP-VF,
DH-HAC-HFW1400RN-VF, HAC-HFW1400RP-VF,
HAC-HFW1400RN-VF, DH-HAC-HFW1400RP-VF-IRE6,
DH-HAC-HFW1400RN-VF-IRE6, HAC-HFW1400RP-VF-IRE6,



HAC-HFW1400RN-VF-IRE6, A21BC0V,
DH-HAC-HFW2231RP-Z-IRE6,DH-HAC-HFW2231RN-Z-IRE6,
HAC-HFW2231RP-Z-IRE6,HAC-HFW2231RN-Z-IRE6,
DH-HAC-HFW2231RP-Z-IRE6-DP,DH-HAC-HFW2231RN-Z-IRE6-DP,
HAC-HFW2231RP-Z-IRE6-DP,HAC-HFW2231RN-Z-IRE6-DP,
DH-HAC-HFW2231RP-Z-IRE6-POC,DH-HAC-HFW2231RN-Z-IRE6-POC,
HAC-HFW2231RP-Z-IRE6-POC,HAC-HFW2231RN-Z-IRE6-POC,
DH-HAC-HFW2231RP-Z,DH-HAC-HFW2231RN-Z,
HAC-HFW2231RP-Z,HAC-HFW2231RN-Z,
A22BC2Z,A22BC9Z,A22BC8Z

I HEREBY CERTIFY THAT :

The sample was received on Aug. 12, 2015 and the testing was carried out on Aug. 19, 2015 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Ray Chou
EMC/RF B.U. Assistant Manager



FCC TEST REPORT

Issued by:

Cerpass Technology Co.,Ltd

No.10, Lane 2, Lianfu Street, Luzhu Township, Taoyuan County 33848, Taiwan(R.O.C.)

Tel: 886-3-322-6888

Fax: 886-3-322-6881

The test record, data evaluation & Equipment. Under Test configurations represented herein are true and accurate accounts of the measurements of the samples EMC characteristics under the conditions specified in this report.

Laboratory Accreditation:

☒ Cerpass Technology Corporation Test Laboratory

NVLAP LAB Code:	200954-0
TAF LAB Code:	1439



Contents

1. Summary of Test Procedure and Test Result.....	6
1.1. Applicable Standards	6
2. Test Configuration of Equipment under Test	7
2.1. Feature of Equipment under Test.....	7
2.2. Test Manner	11
2.3. Description of Test System.....	11
2.4. General Information of Test.....	12
2.5. Measurement Uncertainty	12
3. Test of Conducted Emission.....	13
3.1. Test Limit	13
3.2. Test Procedures	13
3.3. Typical test Setup.....	14
3.4. Measurement Equipment.....	14
3.5. Test Result and Data	15
3.6. Test Photographs	17
4. Test of Radiated Emission	18
4.1. Test Limit	18
4.2. Test Procedures	19
4.3. Typical test Setup.....	20
4.4. Measurement Equipment.....	21
4.5. Test Result and Data (30MHz~1GHz).....	22
4.6. Test Result and Data (1GHz ~6GHz).....	24
4.7. Test Photographs (30MHz ~ 1GHz).....	26
4.8. Test Photographs (1GHz ~ 6GHz)	27
5. Photographs of EUT	28



History of this test report

☐ ORIGINAL.

☒ Additional attachment as following record:

Report No	Version	Date	Description
SEFD1508081	Rev 01	Aug 20, 2015	Initial Issue
SEFD1508081-B	Rev 02	Jul 16, 2016	First edition(Add model name and update standard)
SEFD1607098-A	Rev 03	Aug 29, 2016	Second edition(Add model name)
SEFD1608254-A	Rev 04	Dec 13, 2016	Third edition(Add model name)



1. Summary of Test Procedure and Test Result

1.1. Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in ANSI C63.4 – 2014 and the energy emitted by this equipment was passed Part 2, Part 15, CISPR PUB. 22.

The energy emitted by this equipment was passed both Radiated and Conducted Emissions Class B limits.

Test Item	Normative References	Test Result	Remarks
Conducted Emission	ANSI C63.4-2014 FCC Part 15 Subpart B ICES 003 Issue 6	PASS	Meets Class B Limit Minimum passing margin(QP) is -3.40 dB at 0.3140 MHz
Radiated Emission	ANSI C63.4-2014 FCC Part 15 Subpart B ICES 003 Issue 6	PASS	Meets Class B Limit Minimum passing margin(QP) is -4.50 dB at 35.8200 MHz



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

Third edition

Product Name:	HDCVI CAMERA
Model Name:	DH-HAC-HFW2220RP-VF, DH-HAC-HFW2220RN-VF, HAC-HFW2220RP-VF, HAC-HFW2220RN-VF, DH-HAC-HFW2220RP-VF-IRE6, DH-HAC-HFW2220RN-VF-IRE6, HAC-HFW2220RP-VF-IRE6, HAC-HFW2220RN-VF-IRE6, DH-HAC-HFW2220RP-Z, DH-HAC-HFW2220RN-Z, HAC-HFW2220RP-Z, HAC-HFW2220RN-Z, DH-HAC-HFW2220RP-Z-IRE6, DH-HAC-HFW2220RN-Z-IRE6, HAC-HFW2220RP-Z-IRE6, HAC-HFW2220RN-Z-IRE6, DH-HAC-HFW2120RP-Z, DH-HAC-HFW2120RN-Z, HAC-HFW2120RP-Z, HAC-HFW2120RN-Z, DH-HAC-HFW2120RP-Z-IRE6, DH-HAC-HFW2120RN-Z-IRE6, HAC-HFW2120RP-Z-IRE6, HAC-HFW2120RN-Z-IRE6, DH-HAC-HFW3100R-Z-IRE8, DH-HAC-HFW1200RP-VF, DH-HAC-HFW1200RN-VF, HAC-HFW1200RP-VF, HAC-HFW1200RN-VF, DH-HAC-HFW1200RP-VF-IRE6, DH-HAC-HFW1200RN-VF-IRE6, HAC-HFW1200RP-VF-IRE6, HAC-HFW1200RN-VF-IRE6, DH-HAC-HFW1100RP-VF, DH-HAC-HFW1100RN-VF, HAC-HFW1100RP-VF, HAC-HFW1100RN-VF, DH-HAC-HFW1100RP-VF-IRE6, DH-HAC-HFW1100RN-VF-IRE6, HAC-HFW1100RP-VF-IRE6, HAC-HFW1100RN-VF-IRE6, DH-HAC-HFW1220RP-VF, DH-HAC-HFW1220RN-VF, HAC-HFW1220RP-VF, HAC-HFW1220RN-VF, DH-HAC-HFW1220RP-VF-IRE6, DH-HAC-HFW1220RN-VF-IRE6, HAC-HFW1220RP-VF-IRE6, HAC-HFW1220RN-VF-IRE6, DH-HAC-HFW1400RP-VF, DH-HAC-HFW1400RN-VF, HAC-HFW1400RP-VF, HAC-HFW1400RN-VF, DH-HAC-HFW1400RP-VF-IRE6, DH-HAC-HFW1400RN-VF-IRE6, HAC-HFW1400RP-VF-IRE6, HAC-HFW1400RN-VF-IRE6, A21BC0V, DH-HAC-HFW2231RP-Z-IRE6, DH-HAC-HFW2231RN-Z-IRE6, HAC-HFW2231RP-Z-IRE6, HAC-HFW2231RN-Z-IRE6, DH-HAC-HFW2231RP-Z-IRE6-DP, DH-HAC-HFW2231RN-Z-IRE6-DP, HAC-HFW2231RP-Z-IRE6-DP, HAC-HFW2231RN-Z-IRE6-DP, DH-HAC-HFW2231RP-Z-IRE6-POC, DH-HAC-HFW2231RN-Z-IRE6-POC, HAC-HFW2231RP-Z-IRE6-POC, HAC-HFW2231RN-Z-IRE6-POC, DH-HAC-HFW2231RP-Z, DH-HAC-HFW2231RN-Z, HAC-HFW2231RP-Z, HAC-HFW2231RN-Z, A22BC2Z, A22BC9Z, A22BC8Z
Model Discrepancy:	1) The hardware circuit and shell structure are exactly same, there is only the model names and software are different in some items.



	2) DH-HAC-HFW1100RP-VF-IRE6 was selected as the test model and its data have been recorded in this report.	
Adapter	Model No.:	ADS-12B-1212012Gz
	INPUT:	100-240V~ 50/60Hz Max. 0.3A
	OUTPUT:	12V, 1.0A

Second edition

Product Name:	HDCVI CAMERA	
Model Name:	DH-HAC-HFW2220RP-VF, DH-HAC-HFW2220RN-VF, HAC-HFW2220RP-VF, HAC-HFW2220RN-VF, DH-HAC-HFW2220RP-VF-IRE6, DH-HAC-HFW2220RN-VF-IRE6, HAC-HFW2220RP-VF-IRE6, HAC-HFW2220RN-VF-IRE6, DH-HAC-HFW2220RP-Z, DH-HAC-HFW2220RN-Z, HAC-HFW2220RP-Z, HAC-HFW2220RN-Z, DH-HAC-HFW2220RP-Z-IRE6, DH-HAC-HFW2220RN-Z-IRE6, HAC-HFW2220RP-Z-IRE6, HAC-HFW2220RN-Z-IRE6, DH-HAC-HFW2120RP-Z, DH-HAC-HFW2120RN-Z, HAC-HFW2120RP-Z, HAC-HFW2120RN-Z, DH-HAC-HFW2120RP-Z-IRE6, DH-HAC-HFW2120RN-Z-IRE6, HAC-HFW2120RP-Z-IRE6, HAC-HFW2120RN-Z-IRE6, DH-HAC-HFW3100R-Z-IRE8, DH-HAC-HFW1200RP-VF, DH-HAC-HFW1200RN-VF, HAC-HFW1200RP-VF, HAC-HFW1200RN-VF, DH-HAC-HFW1200RP-VF-IRE6, DH-HAC-HFW1200RN-VF-IRE6, HAC-HFW1200RP-VF-IRE6, HAC-HFW1200RN-VF-IRE6, DH-HAC-HFW1100RP-VF, DH-HAC-HFW1100RN-VF, HAC-HFW1100RP-VF, HAC-HFW1100RN-VF, DH-HAC-HFW1100RP-VF-IRE6, DH-HAC-HFW1100RN-VF-IRE6, HAC-HFW1100RP-VF-IRE6, HAC-HFW1100RN-VF-IRE6, DH-HAC-HFW1220RP-VF, DH-HAC-HFW1220RN-VF, HAC-HFW1220RP-VF, HAC-HFW1220RN-VF, DH-HAC-HFW1220RP-VF-IRE6, DH-HAC-HFW1220RN-VF-IRE6, HAC-HFW1220RP-VF-IRE6, HAC-HFW1220RN-VF-IRE6, DH-HAC-HFW1400RP-VF, DH-HAC-HFW1400RN-VF, HAC-HFW1400RP-VF, HAC-HFW1400RN-VF, DH-HAC-HFW1400RP-VF-IRE6, DH-HAC-HFW1400RN-VF-IRE6, HAC-HFW1400RP-VF-IRE6, HAC-HFW1400RN-VF-IRE6, A21BC0V	
Model Discrepancy:	3) The hardware circuit and shell structure are exactly same, there is only the model names and software are different in some items. 4) DH-HAC-HFW1100RP-VF-IRE6 was selected as the test model and its data have been recorded in this report.	
Adapter	Model No.:	ADS-12B-1212012Gz
	INPUT:	100-240V~ 50/60Hz Max. 0.3A
	OUTPUT:	12V, 1.0A



First edition:

Product Name:	HDCVI CAMERA	
Model Name:	DH-HAC-HFW2220RP-VF, DH-HAC-HFW2220RN-VF, HAC-HFW2220RP-VF, HAC-HFW2220RN-VF, DH-HAC-HFW2220RP-VF-IRE6, DH-HAC-HFW2220RN-VF-IRE6, HAC-HFW2220RP-VF-IRE6, HAC-HFW2220RN-VF-IRE6, DH-HAC-HFW2220RP-Z, DH-HAC-HFW2220RN-Z, HAC-HFW2220RP-Z, HAC-HFW2220RN-Z, DH-HAC-HFW2220RP-Z-IRE6, DH-HAC-HFW2220RN-Z-IRE6, HAC-HFW2220RP-Z-IRE6, HAC-HFW2220RN-Z-IRE6, DH-HAC-HFW2120RP-Z, DH-HAC-HFW2120RN-Z, HAC-HFW2120RP-Z, HAC-HFW2120RN-Z, DH-HAC-HFW2120RP-Z-IRE6, DH-HAC-HFW2120RN-Z-IRE6, HAC-HFW2120RP-Z-IRE6, HAC-HFW2120RN-Z-IRE6, DH-HAC-HFW3100R-Z-IRE8, DH-HAC-HFW1200RP-VF, DH-HAC-HFW1200RN-VF, HAC-HFW1200RP-VF, HAC-HFW1200RN-VF, DH-HAC-HFW1200RP-VF-IRE6, DH-HAC-HFW1200RN-VF-IRE6, HAC-HFW1200RP-VF-IRE6, HAC-HFW1200RN-VF-IRE6, DH-HAC-HFW1100RP-VF, DH-HAC-HFW1100RN-VF, HAC-HFW1100RP-VF, HAC-HFW1100RN-VF, DH-HAC-HFW1100RP-VF-IRE6, DH-HAC-HFW1100RN-VF-IRE6, HAC-HFW1100RP-VF-IRE6, HAC-HFW1100RN-VF-IRE6, DH-HAC-HFW1220RP-VF, DH-HAC-HFW1220RN-VF, HAC-HFW1220RP-VF, HAC-HFW1220RN-VF, DH-HAC-HFW1220RP-VF-IRE6, DH-HAC-HFW1220RN-VF-IRE6, HAC-HFW1220RP-VF-IRE6, HAC-HFW1220RN-VF-IRE6, DH-HAC-HFW1400RP-VF, DH-HAC-HFW1400RN-VF, HAC-HFW1400RP-VF, HAC-HFW1400RN-VF, DH-HAC-HFW1400RP-VF-IRE6, DH-HAC-HFW1400RN-VF-IRE6, HAC-HFW1400RP-VF-IRE6, HAC-HFW1400RN-VF-IRE6	
Model Discrepancy:	5) The hardware circuit and shell structure are exactly same, there is only the model names and software are different in some items. 6) DH-HAC-HFW1100RP-VF-IRE6 was selected as the test model and its data have been recorded in this report.	
Adapter	Model No.:	ADS-12B-1212012Gz
	INPUT:	100-240V~ 50/60Hz Max. 0.3A
	OUTPUT:	12V, 1.0A



Original:

Product Name:	HDCVI CAMERA	
Model Name:	DH-HAC-HFW2220RP-VF, DH-HAC-HFW2220RN-VF, HAC-HFW2220RP-VF, HAC-HFW2220RN-VF, DH-HAC-HFW2220RP-VF-IRE6, DH-HAC-HFW2220RN-VF-IRE6, HAC-HFW2220RP-VF-IRE6, HAC-HFW2220RN-VF-IRE6, DH-HAC-HFW2220RP-Z, DH-HAC-HFW2220RN-Z, HAC-HFW2220RP-Z, HAC-HFW2220RN-Z, DH-HAC-HFW2220RP-Z-IRE6, DH-HAC-HFW2220RN-Z-IRE6, HAC-HFW2220RP-Z-IRE6, HAC-HFW2220RN-Z-IRE6, DH-HAC-HFW2120RP-Z, DH-HAC-HFW2120RN-Z, HAC-HFW2120RP-Z, HAC-HFW2120RN-Z, DH-HAC-HFW2120RP-Z-IRE6, DH-HAC-HFW2120RN-Z-IRE6, HAC-HFW2120RP-Z-IRE6, HAC-HFW2120RN-Z-IRE6, DH-HAC-HFW3100R-Z-IRE8, DH-HAC-HFW1200RP-VF, DH-HAC-HFW1200RN-VF, HAC-HFW1200RP-VF, HAC-HFW1200RN-VF, DH-HAC-HFW1200RP-VF-IRE6, DH-HAC-HFW1200RN-VF-IRE6, HAC-HFW1200RP-VF-IRE6, HAC-HFW1200RN-VF-IRE6, DH-HAC-HFW1100RP-VF, DH-HAC-HFW1100RN-VF, HAC-HFW1100RP-VF, HAC-HFW1100RN-VF, DH-HAC-HFW1100RP-VF-IRE6, DH-HAC-HFW1100RN-VF-IRE6, HAC-HFW1100RP-VF-IRE6, HAC-HFW1100RN-VF-IRE6	
Model Discrepancy:	7) The hardware circuit and shell structure are exactly same, there is only the model names and software are different in some items. 8) DH-HAC-HFW1100RP-VF-IRE6 was selected as the test model and its data have been recorded in this report.	
Adapter	Model No.:	ADS-12B-1212012Gz
	INPUT:	100-240V~ 50/60Hz Max. 0.3A
	OUTPUT:	12V, 1.0A

I/O PORT:

I/O PORT TYPE	Quantity
1). BNC Port	1



2.2. Test Manner

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. Turn on the power of all equipment.
- c. The complete test system included LCD Monitor, DVR and EUT for EMI test.
- d. The test mode of EMI as follow:
Test Mode 1. Normal Operation
The "Test Mode 1" was reported as final data.
- e. The maximum operating frequency is above 108MHz, the test frequency range is from 30MHz to 18GHz.

2.3. Description of Test System

No.	Device	Manufacturer	Model No.	Description
1	LCD Monitor	DELL	SE198WFPT	Non-Shielded,1.8m (R43346)
2	DVR	DAHUA	HCVR5208A	Non-Shielded,1.5m

No.	Cable	Quantity	Description
A	VGA Cable	1	Non-Shielded, 1.8m
B	BNC Cable	1	Shielded,>3.0m



2.4. General Information of Test

Test Site :	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582
FCC Registration Number :	TW1079, TW1061,390316, 228391, 641184
IC Registration Number :	4934B-1, 4934E-1, 4934E-2
VCCI	T-2205 for Telecommunication Test C-4663 for Conducted emission test R-3428, R-4218 for Radiated emission test G-812, G-813 for radiated disturbance above 1GHz
Frequency Range Investigated :	Conducted Emission Test: from 150 kHz to 30 MHz Radiated Emission Test: from 30 MHz to 18,000 MHz
Test Distance :	The test distance of radiated emission below 1GHz from antenna to EUT is 10 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.

2.5. Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE / NEUTRAL	3.25 dB
Radiated Emission	30 MHz ~ 1,000 MHz	Vertical / Horizontal	3.93 dB
	1,000 MHz ~ 18,000 MHz	Vertical / Horizontal	5.18 dB

Test results and Measurement uncertainty without any relationship in the test report.



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2014 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Conducted Emission Limits:

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

3.2. Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

3.3. Typical test Setup




3.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2015.03.29	2016.03.28
AMN	R&S	ESH2-Z5	100182	2014.09.04	2015.09.03
Two-Line V-Network	R&S	ENV216	100325	/	/
ISN	FCC	FCC-TLISN-T2-02	20379	2015.03.29	2016.03.28
ISN	FCC	FCC-TLISN-T4-02	20380	2015.03.29	2016.03.28
ISN	FCC	FCC-TLISN-T8-02	20381	2015.03.29	2016.03.28
ISN	TESEQ	ISN ST08	30175	2015.03.29	2016.03.28
Current Probe	R&S	EZ-17	100303	2015.03.29	2016.03.28
Passive Voltage Probe	R&S	ESH2-Z3	100026	2015.03.29	2016.03.28
Pulse Limiter	R&S	ESH3-Z2	100529	2015.03.29	2016.03.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2015.04.02	2016.04.01
EZ-EMC	Fala	Ver CT3A1	N/A	N/A	N/A



3.5. Test Result and Data

Test Mode :	Mode 1: Normal Operation		
AC Power :	AC 120V/60Hz	Phase :	LINE
Equipment :	HDCVI CAMERA	Model No :	DH-HAC-HFW1100RP-VF-IR E6
Temperature :	25℃	Humidity :	53%
Pressure(mbar) :	1002	Date :	2015/08/15




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3140	10.14	46.32	56.46	59.86	-3.40	QP
2	0.3140	10.14	36.16	46.30	49.86	-3.56	AVG
3	0.5180	10.16	38.99	49.15	56.00	-6.85	QP
4	0.5180	10.16	28.18	38.34	46.00	-7.66	AVG
5	0.6020	10.15	41.63	51.78	56.00	-4.22	QP
6	0.6020	10.15	29.56	39.71	46.00	-6.29	AVG
7	0.8500	10.15	37.46	47.61	56.00	-8.39	QP
8	0.8500	10.15	28.58	38.73	46.00	-7.27	AVG
9	0.9700	10.16	36.39	46.55	56.00	-9.45	QP
10	0.9700	10.16	26.56	36.72	46.00	-9.28	AVG
11	1.2220	10.16	37.38	47.54	56.00	-8.46	QP
12	1.2220	10.16	28.44	38.60	46.00	-7.40	AVG
13	1.7420	10.17	32.96	43.13	56.00	-12.87	QP
14	1.7420	10.17	22.44	32.61	46.00	-13.39	AVG
15	2.5980	10.18	36.06	46.24	56.00	-9.76	QP
16	2.5980	10.18	26.50	36.68	46.00	-9.32	AVG
17	5.3659	10.24	37.20	47.44	60.00	-12.56	QP
18	5.3659	10.24	27.69	37.93	50.00	-12.07	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Normal Operation		
AC Power :	AC 120V/60Hz	Phase :	NEUTRAL
Equipment :	HDCVI CAMERA	Model No :	DH-HAC-HFW1100RP-VF-IR E6
Temperature :	25°C	Humidity :	53%
Pressure(mbar) :	1002	Date :	2015/08/15



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3180	10.14	45.79	55.93	59.76	-3.83	QP
2	0.3180	10.14	36.19	46.33	49.76	-3.43	AVG
3	0.4940	10.15	38.48	48.63	56.10	-7.47	QP
4	0.4940	10.15	27.94	38.09	46.10	-8.01	AVG
5	0.6020	10.16	38.95	49.11	56.00	-6.89	QP
6	0.6020	10.16	27.27	37.43	46.00	-8.57	AVG
7	0.8660	10.17	38.32	48.49	56.00	-7.51	QP
8	0.8660	10.17	28.33	38.50	46.00	-7.50	AVG
9	1.3220	10.18	34.74	44.92	56.00	-11.08	QP
10	1.3220	10.18	24.20	34.38	46.00	-11.62	AVG
11	2.0300	10.18	33.47	43.65	56.00	-12.35	QP
12	2.0300	10.18	23.40	33.58	46.00	-12.42	AVG
13	2.5740	10.19	33.81	44.00	56.00	-12.00	QP
14	2.5740	10.19	22.44	32.63	46.00	-13.37	AVG
15	3.2139	10.20	32.23	42.43	56.00	-13.57	QP
16	3.2139	10.20	21.08	31.28	46.00	-14.72	AVG
17	3.8540	10.22	33.10	43.32	56.00	-12.68	QP
18	3.8540	10.22	22.23	32.45	46.00	-13.55	AVG
19	5.3659	10.26	35.39	45.65	60.00	-14.35	QP
20	5.3659	10.26	24.43	34.69	50.00	-15.31	AVG

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Cerber



3.6. Test Photographs

Front View



Rear View





4. Test of Radiated Emission

4.1. Test Limit

Below 1GHz (for digital device)

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHZ)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHZ)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

(3) The measurement above 1GHz is at close-in distances 3m, and determine the limit L2 corresponding to the close-in distance d2 by applying the following relation: $L2 = L1 (d1/d2)$, where L1 is the specified limit in microvolts per metre (uV/m) at the distance d1 (10m), L2 is the new limit for distance d2 (3m).

So the new Class A limit above 1GHz at 3m is as following table:



Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.75	30
1.75-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

4.2. Test Procedures

Procedure of Preliminary Test

- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 15 cm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.




- Set the spectrum analyzer/ Receiver in the following setting as:
Below 1GHz:
RBW=120KHz / VBW=300KHz / Sweep=AUTO
Above 1GHz:
Peak: RBW=1MHz, VBW=3MHz / Sweep=AUTO
Average: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 or 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.


4.3. Typical test Setup

Below 1GHz Test Setup





Above 1GHz Test Setup




4.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI7	100968	2015.03.29	2016.03.28
Preamplifier	Agilent	87405B	My39500554	2015.03.29	2016.03.28
Preamplifier	Agilent	8449B	3008A02342	2015.03.29	2016.03.28
Bilog Antenna	Sunol Science	JB1	A072414-1	2015.04.22	2016.04.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2015.04.20	2016.04.19
Spectrum Analyzer	R&S	FSP40	100324	2015.03.29	2016.03.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-001	2015.04.02	2016.04.01
EZ-EMC	Fala	Ver CT3A1	N/A	N/A	N/A

**4.5. Test Result and Data (30MHz~1GHz)**

Test Mode :	Mode 1: Normal Operation		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Equipment :	HDCVI CAMERA	Model No :	DH-HAC-HFW1100RP-VF-IR E6
Temp :	23℃	Humidity :	54%
Pressure(mbar) :	1002	Date :	2015/08/16




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	34.8500	-5.26	30.73	25.47	30.00	-4.53	QP	200	169
2	148.3400	-10.56	31.98	21.42	30.00	-8.58	QP	100	198
3	296.7500	-8.13	33.81	25.68	37.00	-11.32	QP	200	350
4	371.4399	-5.69	35.82	30.13	37.00	-6.87	QP	100	147
5	445.1600	-3.80	34.55	30.75	37.00	-6.25	QP	400	126
6	742.9500	2.23	28.00	30.23	37.00	-6.77	QP	100	32

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Normal Operation		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Equipment :	HDCVI CAMERA	Model No :	DH-HAC-HFW1100RP-VF-IR E6
Temp :	23°C	Humidity :	54%
Pressure(mbar) :	1002	Date :	2015/08/16




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	35.8200	-5.26	30.76	25.50	30.00	-4.50	QP	200	1
2	99.8400	-13.63	35.87	22.24	30.00	-7.76	QP	200	360
3	148.3400	-10.56	35.65	25.09	30.00	-4.91	QP	100	15
4	296.7500	-8.13	37.56	29.43	37.00	-7.57	QP	400	63
5	375.3199	-5.56	33.30	27.74	37.00	-9.26	QP	100	20
6	445.1600	-3.80	33.79	29.99	37.00	-7.01	QP	100	152

Note: Measurement Level = Reading Level + Correct Factor



4.6. Test Result and Data (1GHz ~6GHz)

Test Mode :	Mode 1: Normal Operation		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Equipment :	HDCVI CAMERA	Model No :	DH-HAC-HFW1100RP-VF-IR E6
Temp :	23°C	Humidity :	54%
Pressure(mbar) :	1002	Date :	2015/08/16




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1187.000	-8.18	51.83	43.65	74.00	-30.35	peak	100	238
2	1595.000	-5.85	51.78	45.93	74.00	-28.07	peak	100	251
3	1850.000	-3.50	52.94	49.44	74.00	-24.56	peak	100	268
4	2615.000	1.45	51.11	52.56	74.00	-21.44	peak	100	274
5	3703.000	3.21	49.52	52.73	74.00	-21.27	peak	100	272
6	4043.000	4.39	44.26	48.65	74.00	-25.35	peak	200	31

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Normal Operation		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Equipment :	HDCVI CAMERA	Model No :	DH-HAC-HFW1100RP-VF-IR E6
Temp :	23°C	Humidity :	54%
Pressure(mbar) :	1002	Date :	2015/08/16



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1221.000	-8.02	54.52	46.50	74.00	-27.50	peak	100	222
2	1595.000	-5.85	55.84	49.99	74.00	-24.01	peak	100	163
3	1850.000	-3.50	56.55	53.05	74.00	-20.95	peak	100	263
4	2496.000	1.73	49.53	51.26	74.00	-22.74	peak	100	42
5	2649.000	1.36	51.94	53.30	74.00	-20.70	peak	100	36
6	3091.000	0.78	52.43	53.21	74.00	-20.79	peak	200	323


Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Seben



4.7. Test Photographs (30MHz ~ 1GHz)

Front View




Rear View






4.8. Test Photographs (1GHz ~ 6GHz)

Front View



Rear View






5. Photographs of EUT

1) EUT Photo



2) EUT Photo





3) EUT Photo



4) EUT Photo





5) EUT Photo

