16CH Face Recognition NVR

NVR8-16400F(1U)



















DDNS





Analytics









MC	DDEL		NVR8-16400F(1U)
Video		Input	16CH over Network
		Output	HDMI (4K, 1080P), VGA (1080P, 1280x1024, 1024x768)
		Decoding Format	H.265 (HEVC) / H.264
		Decoding Capabilities	1Ch - 8MP ; 4Ch - 2x8MP + 2x5MP ; 9/16Ch - 1MP
Analytics		Analytics Channels	16Ch (Requires supporting IPC)
		Supported Analytics	Face Recognition, Smart Search, Camera Tampering, Line Crossing, Sterile Area, Object Monitoring
		Face Recognition Rate	180 Faces per minute (All Channels) / 5 Faces per second (Single Channel)
Audio		Input	1CH + Depends on Camera Inputs
		Output	1CH + Depends on Camera Outputs
		Two Way Audio	Yes
Bandwidth		Incoming	160Mbps
		Outgoing	160Mbps
е Арр.	Record/ Main Stream	Real-Time Recording	16CH 8MP Real-Time
		8MP	480FPS (NTSC)/400FPS (PAL)
		5MP and lower	480FPS (NTSC)/400FPS (PAL)
οt		Master Streams over Network	Up to 16CH@Recording Resolution
Record / Remote App.	Sub Stream	Resolution	Depends on IPC
		Sub-Streams over Network	Up to Outgoing Bandwidth Capacity
	General	User Access	10 Users Online with Professional Autorithy Management
		Recording Modes	Schedule, Manual, Motion, Sensor, Analytics
ž		Applications	Provision Cam2 for iOS/Android, IE for Windows 7/8/10, Safari for Mac OS, CMS for Windows/MAC
DI.		Playback (Local / Remote)	16CH / 16CH
Playback		Search Mode	Smart Search, Face Recognition, Time-Slice, Time, Event, File Management
D -	-1	USB	1 USB 2.0 Port + 1 USB 3.0 Port
Backup		Backup Format	AVI/DAT
Alarm		Input	Depends on Camera
		Output	Depends on Camera
Storage		HDD	2 SATA (8TB Each)
		E-SATA	No
		RAID	Not Supported
PTZ		Connection	Via Network
		Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
		RS-485	No
Network		Ethernet	1000 Mbps (RJ-45)
		Protocols	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP, FTP, HTTPS
		ONVIF	Yes (For IP Channels)
PoE		Ports	No
		Interface	No
		Standard	No
		Total Power	No
		Max. Power Output (Per Ch.)	No
Others		Power Supply	DC12V/4A
		Power Consumption (No HDD)	5W
		Dimention	W375xD275xH50mm
		Operation Temperature	0°C ~50°C